### TECHNICAL DATA SHEET

## GL.97 glass cloth tape

# h-old. 🌶

#### **Saint-Gobain Tape Solutions**

North America | South America | Europe | Asia For a full list of locations, please visit tapesolutions.saint-gobain.com/contact-us

#### **General Description**

120 micron glass cloth backing coated on one side with an aggressive acrylic adhesive system. Designed for interlayer insulation, banding, lead insulation, holding and general insulation of motors, coils and transformers. Also used in automotive as wire harnessing tape for high temperatures.

#### **Features**

- Good adhesion and tack
- High tensile strength and excellent abrasion resistance
- Excellent resistance to solvents, varnishes, resins, etc.
- High temperature resistance

#### **Technical Data**

Property	Value
Product Type	Single coated
Backing Type	Glass cloth
Adhesive Type	Pure acrylic
Color	White
Backing Thickness	0,12 mm
Total Thickness	0,178 mm
Peel Adhesion at 90° On Steel	4.30 N/cm
Tensile Strength	300.00 N/cm
Rolling Ball Tack	< 10 cm
Elongation at Break	5%
Breakdown Voltage	3.00 kV
Thermal Class	155 (F)
Short Time Temperature Resistance	180 °C
Shelf Life	12 months
Standard Length	50 m
Standard Width	1200 mm



\* International harmonized test methods: ASTM D-1000, PSTC, EN 60454-2.

All statements and information listed above regarding this product are typical values for general guidance, these data have not to be intended as conformity specification. These suggestions are based on tests we believe reliable, but are not guaranteed for accuracy and completeness. The user must test, evaluate and validate this product before the use, assuming risks and liability of such use. This document may be revised without prior notice. Suggested storage temperature is between 10°C and 30°C with 50% relative humidity.

IMPORTANT: It is the user's responsibility to ensure the suitability and safety of Saint-Gobain products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. Saint-Gobain assumes no responsibility for any product failures that occur due to misuse of the materials it provides arising out of the design, fabrication or application of the products into which the materials are incorporated.

WARRANTY: For a period of 12 months, Saint-Gobain warrants this product(s) to be free from defects in manufacturing. The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. SAINT-GOBAIN DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Form #1794EU | © Saint-Gobain May 2021 | h-old is a trademark of Saint-Gobain.

