


AU Power Supply Cord with IEC Connector C13, V-Lock, straight

new



## Description

1 Function:

- Power Cord,
- Protection class I, Pin temperature 70 °C,
- with V-Lock interlocking system

## Weblinks

[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [RoHS](#), [CHINA-RoHS](#), [Mating Connectors](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#), [Accessories](#)

## Technical Data

|                           |                                                                   |
|---------------------------|-------------------------------------------------------------------|
| Ratings IEC               | 10 A / 250 VAC; 50 Hz                                             |
| Dielectric Strength       | > 2 kVDC between L-N<br>> 2 kVAC between L/N-PE<br>(1 min/50 Hz)  |
| Allowable Operation Temp. | -25 °C to 70 °C                                                   |
| Degree of Protection      | from front side IP 20 acc. to IEC 60529                           |
| Protection Class          | Suitable for appliances with protection class I acc. to IEC 61140 |
| Terminal                  | moulded                                                           |
| Material: Housing         | PVC, black                                                        |

|           |                                                                                                                                        |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------|
| Connector | C13 acc. to IEC 60320 IEC 60320-1<br>UL 498, CSA C22.2 no. 42 (for cold conditions) pin-temperature 70 °C,<br>10 A, Protection Class I |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------|

## Variants

| Connector |        |              |                         |            |       | cable     |         |          |          |       | Plug |         |          | Order Number |           |
|-----------|--------|--------------|-------------------------|------------|-------|-----------|---------|----------|----------|-------|------|---------|----------|--------------|-----------|
| Type      | V-Lock | Cord Type    | Conductor cross section | Length [m] | Color | Type      | Country | Standard | Style    | Index | Type | Country | Standard | Style        | Index     |
| C13       | ●      | H05VV-F3G1.0 | 3 x 1 mm <sup>2</sup>   | 2.0        | black | Australia | AU      | AS 3112  | straight | -     |      |         |          |              | 6051.2030 |

Most Popular.

Availability for all products can be searched real-time:<http://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

## Packaging unit

60 Pcs

## Mating Inlets/Plugs shuttered

### Category / Description

[Appliance Inlet Overview complete](#)



|                                                                                                              |      |
|--------------------------------------------------------------------------------------------------------------|------|
| IEC Appliance Inlet C14, Snap-in Mounting, Solder, Quick-connect, Screw or PCB Terminal                      | 6010 |
| IEC Appliance Inlet C14, Screw-on Mounting, Front or Rear Side, Solder or Quick-connect or Screw-on Terminal | 6048 |
| IEC Appliance Inlet C14, Screw-on Mounting, Front Side, Solder or Quick-connect, PCB or Screw Terminal       | 6061 |
| IEC Appliance Inlet C14 or C18, Screw-on Mounting, Rear Side, PCB terminals                                  | GSP1 |
| IEC Appliance Inlet C14 or C18, sandwich Mounting, PCB- or Solder Terminal                                   | GSP2 |

[Appliance Inlet further types to VAC13KS](#)



Power Entry Module Overview complete

|                                                                                              |      |
|----------------------------------------------------------------------------------------------|------|
| IEC Appliance Inlet C14 or C18 with Fuseholder 1- or 2-pole                                  | 4707 |
| IEC Appliance Inlet C14 with Circuit Breaker TA35 2-pole                                     | 6135 |
| IEC Appliance Inlet C14 with Circuit Breaker TA45                                            | 6145 |
| IEC Appliance Inlet C14, with Line Switch 2-pole, Voltage Selector and Fuseholder 1or 2-pole | 6766 |
| IEC Appliance Inlet C14 with Line Switch 1- or 2-pole                                        | DC11 |
| Power Entry Module further types to VAC13KS                                                  | ...  |



Power Entry Module with line filter Overview complete

|                                                                                                              |      |
|--------------------------------------------------------------------------------------------------------------|------|
| IEC Appliance Inlet C14 or C18 with Filter, ECO design, Front- or Rear Side Mounting                         | 5120 |
| IEC Appliance Inlet C14 or C18 with Filter, high attenuation, ECO design, Front- or Rear Side Mounting       | 5123 |
| IEC Appliance Inlet C20 with Filter, ECO design, front or rear side Mounting                                 | 5130 |
| IEC Appliance Inlet C14 with Filter, Circuit Breaker TA45                                                    | 5145 |
| IEC Appliance Inlet C14 with High Frequency Filter, X2Y Technology, ECO design, Front- or Rear Side Mounting | 5150 |
| Power Entry Module with line filter further types to VAC13KS                                                 | ...  |