UNITEDPRO

DC Fan Specification



D4010L05B/S

1. MODEL NUMBER	D4010L05B(X1)	D4010L05S(X1)
2. CATEGORY	BRUSHLESS DC FAN	BRUSHLESS DC FAN
3. FRAME SIZE	40 x 40 x 10 mm (1.6 x 1.6 x 0.4 inch)	40 x 40 x 10 mm (1.6 x 1.6 x 0.4 inch)
4. RATED VOLTAGE	5 VDC	5 VDC
5. OPERATING VOLTAGE RANGE	4 V ~ 5.5V	4 V ~ 5.5V
6. START-UP VOLTAGE	4 V / Min.	4 V / Min.
7. RATED MOTOR SPEED	5000 RPM ±10%	5000 RPM ±10%
8. AIR FLOW	5.3 CFM (0.15 m^3/Min.)	5.3 CFM (0.15 m^3/Min.)
9. STATIC PRESSURE	2.04 mm/H_2O (0.08 inch/H_2O)	2.04 mm/H_2O (0.08 inch/H_2O)
10. RATED CURRENT	0.13 Amp ±10%	0.13 Amp ±10%
11. RATED INPUT POWER	0.65 Watts ±10%	0.65 Watts ±10%
12. NOISE LEVEL	22.69 dB(A)	22.69 dB(A)
13. DIRECTION OF ROTATION	Clockwise viewed from front label	Clockwise viewed from front label
14. OPERATING TEMPERATURE	-10°C ~ + 70°C / 66% (RH)	-10°C ~ + 70°C / 66% (RH)
15. STORAGE TEMPERATURE	-40°C ~ + 75°C / 66% (RH)	-40°C ~ + 75°C / 66% (RH)
16. BEARING SYSTEM	BALL BEARING	SLEEVE BEARING
17.LIFE EXPECTANCY	70,000 Hrs	30,000 Hrs
18. SAFETY APPROVAL	UL, CUL, TUV, CE	UL, CUL, TUV, CE
19. WEIGHT	16 gm	16 gm

