

DC Fan Specification



D6025L12B/S

1. MODEL NUMBER	D6025L12B(X1)
2. CATEGORY	BRUSHLESS DC FAN
3. FRAME SIZE	60 x 60 x 25 mm (2.4 x 2.4 x 1.0 inch)
4. RATED VOLTAGE	12 VDC
5. OPERATING VOLTAGE RANGE	9 V ~15V
6. START-UP VOLTAGE	9 V / Min.
7. RATED MOTOR SPEED	3000 RPM ±10%
8. AIR FLOW	16.0 CFM (0.45 m ³ /Min.)
9. STATIC PRESSURE	2.44 mm/H ₂ O (0.10 inch/H ₂ O)
10. RATED CURRENT	0.10 Amp ±10%
11. RATED INPUT POWER	1.20 Watts ±10%
12. NOISE LEVEL	22.71 dB(A)
13. DIRECTION OF ROTATION	Clockwise viewed from front label
14. OPERATING TEMPERATURE	-10°C ~ + 70°C / 66% (RH)
15. STORAGE TEMPERATURE	-40°C ~ + 75°C / 66% (RH)
16. BEARING SYSTEM	BALL BEARING
17. LIFE EXPECTANCY	70,000 Hrs
18. SAFETY APPROVAL	UL, CUL, TUV, CE
19. WEIGHT	62 gm

D6025L12S(X1)
BRUSHLESS DC FAN
60 x 60 x 25 mm (2.4 x 2.4 x 1.0 inch)
12 VDC
9 V ~15V
9 V / Min.
3000 RPM ±10%
16.0 CFM (0.45 m ³ /Min.)
2.44 mm/H ₂ O (0.10 inch/H ₂ O)
0.10 Amp ±10%
1.20 Watts ±10%
22.71 dB(A)
Clockwise viewed from front label
-10°C ~ + 70°C / 66% (RH)
-40°C ~ + 75°C / 66% (RH)
SLEEVE BEARING
30,000 Hrs
UL, CUL, TUV, CE
62 gm