

DC Fan Specification



D7010M12B/S

- 1. MODEL NUMBER
- 2. CATEGORY
- 3. FRAME SIZE
- 4. RATED VOLTAGE
- 5. OPERATING VOLTAGE RANGE
- 6. START-UP VOLTAGE
- 7. RATED MOTOR SPEED
- 8. AIR FLOW
- 9. STATIC PRESSURE
- 10. RATED CURRENT
- 11. RATED INPUT POWER
- 12. NOISE LEVEL
- 13. DIRECTION OF ROTATION
- 14. OPERATING TEMPERATURE
- 15. STORAGE TEMPERATURE
- 16. BEARING SYSTEM
- 17.LIFE EXPECTANCY
- 18. SAFETY APPROVAL
- 19. WEIGHT

D7010M12B(T1)
BRUSHLESS DC FAN
70 x 70 x 10 mm (2.8 x 2.8 x 0.4 inch)
5 VDC
9 V ~ 15V
15 V / Min.
3200 RPM ±10%
22.2 CFM (0.60 m³/Min.)
2.30 mm/H₂O (0.091 inch/H₂O)
0.25Amp ±10%
3.0 Watts ±10%
31.4dB(A)
Clockwise viewed from front label
-10°C ~ + 70°C / 66% (RH)
-40°C ~ + 75°C / 66% (RH)
BALL BEARING
70,000 Hrs
UL, CUL, TUV, CE
48 gm

D7010M12S(T1)
BRUSHLESS DC FAN
70 x 70 x 10 mm (2.8 x 2.8 x 0.4 inch)
5 VDC
9 V ~ 15V
15 V / Min.
3200 RPM ±10%
22.2 CFM (0.60 m³/Min.)
2.30 mm/H₂O (0.091 inch/H₂O)
0.25 Amp ±10%
3.0 Watts ±10%
31.4 dB(A)
Clockwise viewed from front label
-10°C ~ + 70°C / 66% (RH)
-40°C ~ + 75°C / 66% (RH)
SLEEVE BEARING
30,000 Hrs
UL, CUL, TUV, CE
48 gm