

DC Fan Specification



D8015H12B/S

1. MODEL NUMBER	D8015H12B(X1)
2. CATEGORY	BRUSHLESS DC FAN
3. FRAME SIZE	80 x 80 x 15 mm (3.1 x 3.1 x 0.6 inch)
4. RATED VOLTAGE	12VDC
5. OPERATING VOLTAGE RANGE	9 V ~ 15V
6. START-UP VOLTAGE	9 V / Min.
7. RATED MOTOR SPEED	3000 RPM ±10%
8. AIR FLOW	30.2 CFM (0.86 m ³ /Min.)
9. STATIC PRESSURE	2.66 mm/H ₂ O (0.10 inch/H ₂ O)
10. RATED CURRENT	0.17 Amp ±10%
11. RATED INPUT POWER	2.28 Watts ±10%
12. NOISE LEVEL	31.06 dB(A)
13. DIRECTION OF ROTATION	Clockwise viewed from front label
14. OPERATING TEMPERATURE	-10°C ~ + 70°C / 66% (RH)
15. STORAGE TEMPERATURE	-40°C ~ + 75°C / 66% (RH)
16. BEARING SYSTEM	BALL BEARING
17.LIFE EXPECTANCY	50,000 Hrs
18. SAFETY APPROVAL	UL, CUL, TUV, CE
19. WEIGHT	40 gm

D8015H12S(X1)
BRUSHLESS DC FAN
80 x 80 x 15 mm (3.1 x 3.1 x 0.6 inch)
12VDC
9 V ~ 15V
9 V / Min.
3000 RPM ±10%
30.2 CFM (0.86 m ³ /Min.)
2.66 mm/H ₂ O (0.10 inch/H ₂ O)
0.17 Amp ±10%
2.28 Watts ±10%
31.06 dB(A)
Clockwise viewed from front label
-10°C ~ + 70°C / 66% (RH)
-40°C ~ + 75°C / 66% (RH)
SLEEVE BEARING
25,000 Hrs
UL, CUL, TUV, CE
40 gm