



ChainMate® Chain & Wire Rope Moly Lubricant



FEATURES

- Fortified with molybdenum disulfide
- A more focused spray pattern for superior penetration to the core of wire ropes
- Effective under extreme pressure and temperature ranges
- A more robust composition with foaming action to resist over spray
- Increases chain and wire rope life
- Reduces wear caused by friction and corrosion
- Provides maximum lubrication and corrosion protection
- High adhesion
- Use with guards in place to eliminate costly down time
- VOC compliant in all 50 states



APPLICATIONS

- Bushings
- Cables
- Chains
- Cranes
- Cutting tools
- Drag lines
- Drives
- Forklifts
- Pins
- Pulleys
- Rollers
- Saws
- Sprockets
- Wire ropes

iS (IDENTIFICATION SYSTEM)



AVAILABLE PRODUCTS

Part No.	Net Contents	Container	Case Pack	Case Wt.
02416	11 wt. oz. (312 g)	Aerosol	12	12 lbs.



ChainMate® Chain & Wire Rope Moly Lubricant

PROPERTIES

Appearance/physical state	Liquid	Color	Dark grey, black
Odor	Slight petroleum	Flash point	<-4.0°F (<-20.0°C)TCC
Vapor pressure	35 psi @ 75°F(23.9°C)	Vapor density	> 1
Solubility (water)	16%	Viscosity	150 cP @ 75°F(23.9°C)
Density	7.32	Heat of combustion	>30 kJ/g
Percent volatile	17%	VOC	22.33% per US State & Federal Consumer Product Regulations
Specific gravity	0.88 @ 20°C		

HANDLING AND STORAGE

Mix well before using. Spray on clean surface. Use attached extension tube for pinpoint application. Safe to use on plastic, rubber and paint. Use only in well ventilated areas. Avoid all sources of ignition (spark or flame).

Keep container in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store between 40°F (5°C) and 120°F (49°C). Store aerosols as Level 3 Aerosol (NFPA 30B). Store all materials in a dry, well-ventilated area. Avoid breathing vapors

DISPOSAL

Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations.



800.241.8334 | www.lpslabs.com

TDS00116 160615