



# Force 842° Dry Moly Lubricant



## FEATURES

- Works under extreme temperatures (842°F) and pressures (100,000 psi)
- Dry film resists dirt and dust
- Provides excellent water and chemical resistance
- High adhesion
- Use for assembly and break-in lubrication
- Prevents seizures



## APPLICATIONS

- Aircraft Landing Gear
- Brake Adjustment Screws
- Forklift Channels
- Fire Doors
- Oven Chains and Cables
- Oven Dolleys
- Overhead Crane Rail
- Planting Hooks in Ovens
- Sliding Surfaces
- Rollers

iS (IDENTIFICATION SYSTEM)



## AVAILABLE PRODUCTS

Part No.	Net Contents	Container	Case Pack	Case Wt.
02516	11 wt. oz. (312 g)	Aerosol	12	12 lbs.



# Force 842° Dry Moly Lubricant

## PROPERTIES

Appearance/physical state	Liquid	Color	Dark grey, black
Odor	Characteristic	Flash point	<1.4°F° (<-17.0°C)TCC
Solubility (water)	<25% by weight	Percent volatile	<14 cSt
Boiling point/range	141.8 °F (61 °C)	Evaporation rate	<1 (Ethyl Ether = 1)
Vapor pressure	352.53 MM HG @38°C	Vapor density	~3
Partition coefficient	>1	Heat of combustion	>30 kJ/g
Flammability limit	lower 0.6% upper 7%	VOC	95% per US State and Federal Consumer Product Regulations

## HANDLING AND STORAGE

Mix well before using. Spray on clean surface. Use attached extension tube for pinpoint application. Safe to use on plastic, rubber and paint. Use only in well ventilated areas. Avoid all sources of ignition (spark or flame).

Keep container in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store between 40°F (5°C) and 120°F (49°C). Store aerosols as Level 3 Aerosol (NFPA 30B). Store all materials in a dry, well-ventilated area. Avoid breathing vapors

## DISPOSAL

Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations.



800.241.8334 | [www.lpslabs.com](http://www.lpslabs.com)

TDS01916 160616