



CRC MOTOR STARTER

Ref. : 10510

1. GENERAL DESCRIPTION

Professional grade engine starting fluid.

A balanced formulation combining active, volatile solvents, upper cylinder lubricant and corrosion inhibitors, each designed to play a vital part in starting engines. The ingredients are carefully blended to ensure the correct type of initial starting in the combustion chamber and to promote immediate combustion.

2. FEATURES

- High volatility provides the necessary fuel vapours to obtain a combustible air/fuel mixture, even at low temperatures and high humidity.
- Ensures fast, economical starting of all diesel and gasoline engines.
- Reduces starter motor and spark plug wear.
- Saves battery strain and engine wear during cold start.
- Saves time and money.
- An essential tool, particularly in winter, after long periods of standstill and under humid climatic conditions.
- Aerosols use propane propellant to maintain high pressure to the very last fluid in the can. Equipped with the 360° (upside - down) spray valve and extension tube for added convenience.

3. APPLICATIONS

- | | |
|------------------------------|---|
| • Cars | • Boats (in-board and out board) |
| • Trucks | • Go-carts |
| • Busses | • Stationary engines |
| • Tractors | • Compressors |
| • Motorbikes and motorcycles | • Diesel, gasoline and kerosene engines |
| • Chain saws | |

4. DIRECTIONS

- Spray briefly into air intake or filter, giving the product some time to evaporate.
- Accelerate slightly during starting.
- Repeat if necessary.
- The use of choke (for gasoline engines) and glow plugs (for diesel engines) is not necessary.
- Use only until engine is started. Do not use in confined areas.
- Always follow the recommendations in the instruction manual of the engine manufacturer.
- A safety data sheet (MSDS) according EU directive 93/112 is available for all CRC products.



Manufactured by :
CRC Industries Europe NV
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com





CRC MOTOR STARTER

Ref. : 10510

5. TYPICAL PRODUCT DATA (without propellant)

Appearance	: colourless liquid
Odour	: typical
Specific gravity @ 20°C	: 0,71
Boiling range (solvents)	: 35-70°C
Flash point (closed cup)	: < -30°C
Evaporation rate (vs. ether = 1)	: 1,1
Vapour density (vs. air = 1)	: 2,6
Explosion limits	: 1-45%

6. PACKAGING

aerosol : 12 x 200 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10510 03 0197 01
Date : 23 september 2003



Manufactured by :
CRC Industries Europe NV
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com

