

ROST FLASH PRO

Technical Data Sheet

Product name: Rost Flash Pro
Sales code: 32720

Creation date: 8/2016

Version: I

1: General description

Freezes and cracks rust!

1. Rust layer on a bolt.
2. When sprayed, the rust cools down by 40°C and cracks, leaving small fissures.
3. Penetration of the active liquids.
4. Blocked parts are separated easily.

Rost Flash Pro loosens all kind of threaded parts, hinges and sliding parts. Rost Flash Pro is free of silicones and acids.

2: Features

- Cracks the layer of rust and dirt using thermal shock (reduces temperature by 40°C).
- Loosens metal parts seized by dirt, corrosion or dried-up grease.
- Penetrates quickly.
- Does not contain silicones.
- Safe on all metal surfaces, does not stain.
- Safe on most rubbers, plastics and coatings. Test on sensitive or stressed materials before use.
- Convenient 360° (including inverted position) spray valve for aerosols.

3: Applications

- Cleaning mechanical parts.
- Handling equipment.
- Seized and corroded parts.
- Agricultural equipment.
- General disassembly.

4: Directions

- Remove most of the loose dirt with a wire brush.
- Spray liberally and allow to run off.
- Use extension tube for more precise application.
- Spray from a short distance.
- Allow a few minutes for good penetration.
- Repeat if necessary.
- To remove residues or excess product, use CRC Power Clean Pro.
- A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.



5: Typical product data (without propellant)

- Appearance : Liquid
- Color : amber
- Odour : Characteristic odor
- Density : 0.74 g/cm³ (@ 20°C)
- Flash Point : < 0 °C
- Operating temperature active product : temp. drop -40 °C
- Horizontal spread active product : 19 (after 120 s) cm²

6: Packaging

Aerosol

12x500 ML

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.