



TKX[®] ALL-PURPOSE LUBRICANT



FEATURES

- Excellent multi-purpose lubricant
- Loosens rusted or frozen parts
- Displaces moisture
- Protects against corrosion
- Provides a non-drying, long lasting, oily film
- High flash point of >160°F (71°C)
- Does not contain chlorinated solvents or silicones
- Non-conductive
- Nonfood Compounds Program Listed
Category Code: H2 Registration #059842 (Aerosol); #059843 (Bulk)



APPLICATIONS

- Bearings
- Cables and Chains
- Castings
- Dies and Molds
- Forgings
- Gears
- Machined Stock
- Machinery
- Nuts and Bolts
- Pumps
- Pulleys
- Saw Blades
- Springs
- Stalled Engines
- Ways and Guides
- Wheels

IS (IDENTIFICATION SYSTEM)



AVAILABLE PRODUCTS

Part No.		Net Contents	Container	Case Pack	Case Wt.
US	Canada				
02016	C02016	11 wt. oz. (312 g)	Aerosol	12	12 lbs.
02022	C02022	20 fl.oz. (591 mL)	Trigger	12	18 lbs.
02028	C02028	1 gal. (3.78 L)	Container	4	35 lbs.
02005	C02005	5 gal. (18.93 L)	Pail	1	38 lbs.
02055	C02055	55 gal. (208 L)	Drum	1	385 lbs.



TKX[®] ALL-PURPOSE LUBRICANT

PROPERTIES

Appearance/ Physical State	Liquid	Color	Dark green
Odor	Vanilla. Slight petroleum	Flash point	163.4°F (73.0°C)TCC
Solubility (water)	<3%	Auto-ignition Temperature	>442.4°F (>228°C)
Initial Boiling Point	417.2°F (214°C)	Vapor Pressure	<0.05 mm Hg@20°C
Viscosity	<7cSt @20°C	Type Propellant	Carbon Dioxide
Specific gravity	0.83 - 0.85 @ 20°C	Dielectric Strength	> 42 kV
Surface Tension	24.4 dynes/cm	Pour Point	< -50°F (-46°C)
Temperature Range °F(°C)	-50°F to 300°F (-46°C to 149°C)	Flammability Limit	lower 0.6% upper 7%
VOC	2.5 % per US State & Federal Consumer Product Regulations		

DIRECTIONS

Shake well before using. Spray on clean surface. Use the attached extension tube for pinpoint application.

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not re-use empty containers. Do not breathe gas. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling.

STORAGE

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Protect from freezing.

DISPOSAL INFORMATION

Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.lpslabs.com

©2017 ITW Pro Brands • LPS[®] and TKX[®] are registered trademarks of Illinois Tool Works All Rights Reserved • TDS02016 • 170505