Safety Data Sheet

Material: 60003720 **ELASTOSIL® E4** TRANSPARENT Version: 1.3 (INTL-GHS) Date of print: 02.03.2020 Date of last alteration: 20.11.2019 SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1 Product identifier **Commercial product name: ELASTOSIL® E4** TRANSPARENT 1.2 Relevant identified uses of the substance or mixture and uses advised against Use of substance / preparation: Industrial. Adhesive / sealant 1.3 Details of the supplier of the safety data sheet Manufacturer/distributor: Wacker Chemie AG Street/POB-No.: Hanns-Seidel-Platz 4 State/postal code/city: D 81737 München Telephone: +49 89 6279-0 Telefax: +49 89 6279-1770 Information about the Safety Data Sheet: +49 8677 83-4888 Telephone Telefax +49 8677 886-9722 eMail WLCP-MSDS@wacker.com 1.4 **Emergency telephone number Emergency Information:** Europe +44 1235 239670 **Emergency Information:** Africa and the Middle East except +44 1235 239671 Bahrain **Emergency Information:** Bahrain +973 1619 8321 **Emergency Information:** Caribbean, Central America and South +1 646 844 7309 America except Chile and Colombia **Emergency Information:** Chile +56 2 2582 9336 **Emergency Information:** Colombia +57 1 508 7337 **Emergency Information:** East Asia and Southeast Asia except +65 3158 1074 Sri Lanka, Bangladesh and Pakistan **Emergency Information:** Sri Lanka +65 3158 1195 **Emergency Information:** Bangladesh +65 3158 1200

SECTION 2: Hazards identification

Emergency Information:

2.1 Classification of the substance or mixture

Not a hazardous substance or mixture.

2.2 Label elements

No labeling according to GHS required.

Code	Additional Labelling
EUH210	Safety data sheet available on request.

Pakistan

+65 3158 1329

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

not applicable

Safety Data Sheet

Material: 60003720

ELASTOSIL® E4 TRANSPARENT

Version: 1.3 (INTL-GHS)

Date of print: 02.03.2020

Date of last alteration: 20.11.2019

3.2 Mixtures

3.2.1 Chemical characteristics

Polydimethylsiloxane and fillers and auxiliaries and acetoxysilane cross-linker

3.2.2 Hazardous ingredients

EC-No.	CAS No.	Substance	Content %
241-677-4	17689-77-9	Triacetoxyethylsilane	<2,5
224-221-9	4253-34-3	Triacetoxymethylsilane	<2
		Oligomeric ethyl and methyl acetoxysilanes	<2

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) in amounts above \geq 0.1%.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In case of accident or if you feel unwell seek medical advice (show label or SDS where possible).

After contact with the eyes:

Rinse immediately with plenty of water. Seek medical advice in case of continuous irritation.

After contact with the skin:

Wipe off excess material with cloth or paper. Wash with plenty of water or water and soap. In the event of a visible skin change or other complaints, seek medical advice (show label or SDS where possible).

After inhalation:

Material cannot be inhaled under normal conditions.

After swallowing:

Give several small portions of water to drink. Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Any relevant information can be found in other parts of this section.

4.3 Indication of any immediate medical attention and special treatment needed

Further toxicology information in section 11 must be observed.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

alcohol-resistant foam, carbon dioxide, water mist, sprinkler system, sand, extinguishing powder.

Extinguishing media which must not be used for safety reasons: water jet .

5.2 Special hazards arising from the substance or mixture

Risk of hazardous gasses or fumes in the event of fire. Exposure to combustion products may be a health hazard! Hazardous combustion products: toxic and very toxic fumes .

5.3 Advice for firefighters

Special protective equipment for fire fighting:

Use respiratory protection independent of recirculated air. Keep unprotected persons away.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols. If material is released indicate risk of slipping. Do not walk through spilled material.

Safety Data Sheet

Material: 60003720

ELASTOSIL® E4 TRANSPARENT

Version: 1.3 (INTL-GHS)

Date of print: 02.03.2020

Date of last alteration: 20.11.2019

6.2 Environmental precautions

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

6.3 Methods and material for containment and cleaning up

Scoop up large quantities after dusting surfaces with sand or Fuller's earth to prevent sticking. Sweep or scrape up the spilled material and place in an appropriate chemical waste container. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Apply sand or other inert granular material to improve traction.

Further information:

Exhaust vapours. Eliminate all sources of ignition. Consider explosion protection. Observe notes under section 7.

6.4 Reference to other sections

Relevant information in other sections has to be considered. This applies in particular for information given on personal protective equipment (section 8) and on disposal (section 13).

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Precautions for safe handling:

Ensure adequate ventilation. Must be syphoned off in situ. Keep away from incompatible substances in accordance with section 10. Observe information in section 8.

Precautions against fire and explosion:

Product may release acetic acid. Flammable vapors may accumulate and form explosive mixtures with air in containers, process vessels, including partial, empty and uncleaned containers and vessels, or other enclosed spaces. Keep away from sources of ignition and do not smoke. Take precautionary measures against electrostatic charging. Cool endangered containers with water.

7.2 Conditions for safe storage, including any incompatibilities

Conditions for storage rooms and vessels:

Observe local/state/federal regulations.

Advice for storage of incompatible materials:

Observe local/state/federal regulations.

Further information for storage:

Store in a dry and cool place. Protect against moisture. Store container in a well ventilated place.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.2 Exposure controls

8.2.1 Exposure in the work place limited and controlled

General protection and hygiene measures:

Observe standard industrial hygiene practices for the handling of chemical substances. Do not inhale gases/vapours/aerosols. Use with adequate ventilation. Avoid contact with eyes and skin. Preventive skin protection recommended. Remove contaminated, soaked clothing immediately. Clean work areas regularly. Provide emergency shower and eye-bath. Do not eat, drink or smoke when handling.

Personal protection equipment:

Respiratory protection

Safety Data Sheet

Material: 60003720

ELASTOSIL® E4 TRANSPARENT

Version: 1.3 (INTL-GHS)

Date of print: 02.03.2020

Date of last alteration: 20.11.2019

If inhalative exposure above the occupational exposure limit cannot be excluded, adequate respiratory protection equipment must be used. Suitable respiratory equipment: Respirator with a full face mask, according to acknowledged standards such as EN 136. Recommended Filter type: Gas filter type ABEK (certain inorganic, organic and acidic gases and vapors; ammonia/amines), according to acknowledged standards such as EN 14387

Observe the equipment manufacturer's information and wear time limits for respirators.

Eye protection

protective goggles .

Hand protection

Gloves are required at all times when handling the material.

Recommended glove types: Protective gloves made of butyl rubber thickness of the material: > 0,3 mm Breakthrough time: > 480 min

Recommended glove types: Protective gloves made of nitrile rubber thickness of the material: > 0,1 mm Breakthrough time: 60 - 120 min

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Note that, due to the numerous external influences (such as temperature), a chemically resistant protective glove in daily use may have a service life that is considerably shorter than the measured break through time.

Skin protection

protective clothing.

8.2.2 Exposure to the environment limited and controlled

Prevent material from entering surface waters, drains or sewers and soil.

8.3 Further information for system design and engineering measures

Observe information in section 7. Observe national regulatory requirements.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Property:	Value:	Method:
Appearance		
Physical state	liquid	
Form	paste	
Colour:	colourless	
Odour		
Odour:	pungent	
Odour limit		
Odour limit	no data available	
pH-Value		
pH-Value	not applicable	
Melting point/freezing point		
Melting point / melting range	not applicable	
Initial boiling point and boiling range		
Boiling point / boiling range	not applicable	
Flash point		
Flash point	not applicable	
Evaporation rate		
Evaporation rate	no data available	
Upper/lower flammability or explosive limits		
Lower explosion limit (LEL)	not applicable	
Upper explosion limit (UEL)	not applicable	
Vapour pressure		
Vapour pressure	not applicable	

Safety Data Sheet

Material: 60003720

ELASTOSIL® E4 TRANSPARENT

Versior	: 1.3 (INTL-GHS)	Date of print: 02.03.2020	Date of last alteration: 20.11.2019
	Solubility(ies)		
	Water solubility / miscibility	: virtually insoluble	
	Vapour density		
	Relative gas/vapour density	: No data known.	
	Relative Density		
	Relative Density	: 1,01 (20 °C)	(DIN 53217)
	,	(Water / 4 $^{\circ}C = 1,00$)	
	Density	: 1,01 g/cm ³ (20 °C)	(DIN 53217)
	Partition coefficient: n-octanol/water		
	Partition coefficient: n-octanol/water	: No data known.	
	Auto-ignition temperature		
	Ignition temperature	: 440 °C	(-)
	Decomposition temperature		
	Thermal decomposition	: not applicable	
	Viscosity		
	Viscosity (dynamic)	: not applicable	
	Molecular mass		
	Molecular mass	: not applicable	
~ ~			

9.2 Other information

Solubility in water: Hydrolytic decomposition occurs. pH Value: Product displays acidic reaction with water. Explosion limits for released acetic acid: 4 - 17%(V).

SECTION 10: Stability and reactivity

10.1 – 10.3 Reactivity; Chemical stability; Possibility of hazardous reactions

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

Relevant information can possibly be found in other parts of this section.

10.4 Conditions to avoid

moisture, Heat, open flames, and other sources of ignition.

10.5 Incompatible materials

Reacts with: water , basic substances and alcohols . Reaction causes the formation of: acetic acid .

10.6 Hazardous decomposition products

By hydrolysis: acetic acid . Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 $^{\circ}$ C (302 $^{\circ}$ F) through oxidation.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

11.1.1 Acute toxicity

Product details:

Route of exposure	Result/Effect	Species/Test system	Source
Oral	LD50: > 2000 mg/kg	Rat	Conclusion by analogy
dermal	LD50: > 2009 mg/kg	Rabbit	Conclusion by analogy

11.1.2 Skin corrosion/irritation

Product details:

Result/Effect	Species/Test system	Source
not irritating	Rabbit	Conclusion by
		analogy

11.1.3 Serious eye damage / eye irritation

Safety Data Sheet

Material: 60003720

ELASTOSIL® E4 TRANSPARENT

Version: 1.3 (INTL-GHS)

Date of print: 02.03.2020

Date of last alteration: 20.11.2019

Product details:

Result/Effect	Species/Test system	Source
not irritating	in vitro assay; Bovine eye /	Conclusion by
	bovine cornea	analogy
		OECD 437
not irritating	Rabbit	Conclusion by
		analogy

11.1.4 Respiratory or skin sensitization

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.5 Germ cell mutagenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.6 Carcinogenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.7 Reproductive toxicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.8 Specific target organ toxicity (single exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.9 Specific target organ toxicity (repeated exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.10 Aspiration hazard

Assessment:

Based on the physical-chemical properties of the product no aspiration hazard must be expected.

11.1.11 Further toxicological information

In contact with dampness product separates a small quantity of acetic acid (64-19-7) which irritates skin and mucous membranes.

SECTION 12: Ecological information

12.1 Toxicity

Assessment:

Assessment based on ecotoxicological tests with similar products under consideration of the physical-chemical properties: For this product no effects on aquatic organisms, relevant for classification, are expected. According to current knowledge adverse effects on water purification plants are not expected.

12.2 Persistence and degradability

Assessment:

Silicone content: biologically not degradable. Separation by sedimentation. The product of hydrolysis (acetic acid) is readily biodegradable.

Safety Data Sheet

Material: 60003720

ELASTOSIL® E4 TRANSPARENT

Version: 1.3 (INTL-GHS)

Date of print: 02.03.2020

Date of last alteration: 20.11.2019

12.3 Bioaccumulative potential

Assessment:

Polymer component: Bioaccumulation is not expected to occur.

12.4 Mobility in soil

Assessment:

Silicone content: Insoluble in water.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

none known

12.7 Additional information

In cross-linked state not soluble in water. Easily separable from water by filtration.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

13.1.1 Material

14.5

14.6

Recommendation:

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

13.1.2 Uncleaned packaging

Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

SECTION 14: Transport information

14.1 – 14.4 UN number; UN proper shipping name; Transport hazard class(es); Packing group

Road ADR: Valuation:	Not regulated for transport
Railway RID: Valuation:	Not regulated for transport
Transport by sea IMDG-Code: Valuation	Not regulated for transport
Air transport ICAO-TI/IATA-DGR: Valuation	Not regulated for transport
Environmental hazards	
Hazardous to the environment: no	
Special precautions for user	

Relevant information in other sections has to be considered.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Bulk transport in tankers is not intended.

Safety Data Sheet

Material: 60003720

ELASTOSIL® E4 TRANSPARENT

Version: 1.3 (INTL-GHS)

Date of print: 02.03.2020

Date of last alteration: 20.11.2019

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National and local regulations must be observed.

For information on labelling please refer to section 2 of this document.

15.2 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

Australia:	AICS (Australian Inventory of Chemical Substances):
	This product is listed in, or complies with, the substance inventory.
China:	IECSC (Inventory of Existing Chemical Substances in China):
Canada:	This product is listed in, or complies with, the substance inventory.
Canada	This product is listed in, or complies with, the substance inventory.
Philippines:	PICCS (Philippine Inventory of Chemicals and Chemical Substances):
	This product is listed in, or complies with, the substance inventory.
United States of America (USA):	TSCA (Toxic Substance Control Act Chemical Substance Inventory):
	All components of this product are listed as active or are in compliance with the
	substance inventory.
Taiwan:	TCSI (Taiwan Chemical Substance Inventory):
	This product is listed in, or complies with, the substance inventory. General note:
	The Taiwanese chemicals regulation requires a phase 1 registration for TCSI-listed
	or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan
	exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each
	ingredient). It is the duty of the importing/manufacturing legal entity to take care of
European Economic Area (EEA)::	this obligation.
European Economic Area (EEA)	General note: the registration obligations for substances imported into the EEA or
	manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by
	the said supplier. The registration obligations for substances imported into the EEA
	by customers or other downstream users must be fulfilled by the latter.
South Korea (Republic of Korea):	AREC (Act on Registration and Evaluation of Chemicals; "K-REACH"):
	General note: in case of registration obligations for substances or polymers
	imported into Korea or manufactured within Korea these are fulfilled by the supplier
	mentioned in section 1. The registration obligations for substances or polymers
	imported into Korea by customers or other downstream users must be fulfilled by
	the latter.

SECTION 16: Other information

16.1 Material

The details in this document are based on the state of our knowledge at the time of revision. They do not constitute an assurance of the described product properties in terms of statutory warranty requirements.

The providing of this document to a recipient does not relieve the recipient of his or her responsibility toward compliance with all laws and stipulations applicable to the product. This applies in particular to the further sale or distribution of the product or substances or items containing the product, in other jurisdictions and with regard to the protection of third-party intellectual property rights. If the described product is processed or mixed with other substances or materials, the details stated in this document cannot be conferred to the resultant new product unless this has been expressly mentioned. If the product is repackaged, the recipient is obligated to additionally provide the required safety-related information.

WACKER restricts the use of its products inside the human body or in contact with bodily fluids and mucosa. For further details please review our Health Care Policy on www.wacker.com. WACKER may cancel any delivery obligation(s) if the Health Care Policy is not observed.

16.2 Further information:

Commas appearing in numerical data denote a decimal point. Vertical lines in the left-hand margin indicate changes compared with the previous version. This version supersedes all previous versions.

Safety Data Sheet

Material: 60003720

ELASTOSIL® E4 TRANSPARENT

Version: 1.3 (INTL-GHS)

Date of print: 02.03.2020

Date of last alteration: 20.11.2019

- End of Safety Data Sheet -