

## Your go-to tape for greater design possibilities.

- Solventless adhesive technology
- High initial tack
- ► High thermal and humidity resistance
- High peel performance on a wide range of surfaces
- Superior high-temperature shear performance
- Adhesion to a wide variety of substrates ranging from metals to some plastics
- Easy handling and converting due to filmic liner delivery
- Perfect for a variety of markets, including consumer appliances, industrial machinery, transportation, consumer electronics

Bonds to many high surface energy substrates and some low surface energy substrates, including:

- Stainless steel
- ▶ HDPE
- ► ABS
- Acrylic
- ▶ PP
- ► Polycarbonate
- Aluminium
- ▶ Glass

## Creating designs in applications.

Rising to the challenge in many markets including consumer appliances, industrial machinery, transportation, signage, general industrial and consumer electronics.













- ► POP/POS displays
- Light boxes
- ► Indoor/outdoor signs
- Paper bonding and packaging

- Metal fabrication
- Splicing and bonding
- Sports equipment
- ► Home decoration
- Trim attachment in appliance

- Mounting of plastic parts
- Mounting in electronics
- Furniture trim attachment

## The next generation of thin bonding.



## 3M™ GPT-020F Double Coated Tape

GPT-020F		
Adhesive	Solventless acrylic	
Carrier type (thickness)	PET 12 micron	
Liner type (thickness)	White PP 100 micron	
Total tape thickness without liner	200 micron	
Short term temp. performance	190°C	
Long term temp. performance	90°C	
Colour	Transparent	

For more information, please visit: www.3M.co.uk/tapes