

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Trade name or designation of the mixture** Dykem® Cross Check™ Torque Seal® - Pink

**Registration number** -

**Synonyms** None.

**Part Number** 83320

**Issue date** 30-December-2020

**Version number** 04

**Revision date** 14-June-2021

**Supersedes date** 08-June-2021

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Inspection Paint

**Uses advised against** None known.

### 1.3. Details of the supplier of the safety data sheet

#### Supplier

**Company name** AlSCO Ltd  
**Address** Unite 13 Hillmead Industrial Estate  
Marshall Road  
Swindon, Wiltshire  
United Kingdom SN5 5FZ

**Telephone** + 44 1793 733900 (09.00-17.00)

**In Case of Emergency** National Poisons Information Service +44 344 892 0111

**E-mail** info@alscoltd.co.uk

#### Manufacturer

**Company name** ITW Pro Brands  
**Address** 805 E. Old 56 Highway  
Olathe, KS 66061

**Country** (U.S.A.)

**Telephone** +1 800-443-9536

**In Case of Emergency** 1-800-535-5053

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

##### Physical hazards

Flammable liquids	Category 3	H226 - Flammable liquid and vapour.
-------------------	------------	-------------------------------------

##### Health hazards

Serious eye damage/eye irritation	Category 1	H318 - Causes serious eye damage.
Skin sensitisation	Category 1	H317 - May cause an allergic skin reaction.
Germ cell mutagenicity	Category 1B	H340 - May cause genetic defects.
Carcinogenicity	Category 2	H351 - Suspected of causing cancer.
Specific target organ toxicity - repeated exposure	Category 1 (central nervous system)	H372 - Causes damage to organs (central nervous system) through prolonged or repeated exposure.
Aspiration hazard	Category 1	H304 - May be fatal if swallowed and enters airways.

**Environmental hazards**

Hazardous to the aquatic environment,  
long-term aquatic hazard

Category 3

H412 - Harmful to aquatic life with  
long lasting effects.

**Hazard summary**

May be ignited by heat, sparks or flames. May be fatal if swallowed and enters airways. Causes serious eye damage. Causes damage to organs through prolonged or repeated exposure. Suspected of causing cancer. May cause an allergic skin reaction. May cause genetic defects. Prolonged exposure may cause chronic effects.

**2.2. Label elements****Label according to Regulation (EC) No. 1272/2008 as amended****Contains:**

2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime, 2-Methoxy-1-methylethyl acetate, CARBENDAZIM (ISO); METHYL BENZIMIDAZOL-2-YLCARBAMATE, Diacetone alcohol, Ethylbenzene, SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH.; STRAIGHT RUN KEROSENE [A COMPLEX COMBINATION OF HYDROCARBONS OBTAINED FROM THE DISTILLATION OF CRUDE OIL OR NATURAL GASOLINE. IT CONSISTS PREDOMINANTLY OF SATURATED HYDROCARBONS HAVING CARBON NUMBERS PREDOMINANT

**Hazard pictograms****Signal word**

Danger

**Hazard statements**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H340	May cause genetic defects.
H351	Suspected of causing cancer.
H372	Causes damage to organs (central nervous system) through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements****Prevention**

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe vapour.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

**Response**

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTRE/doctor.
P331	Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE/doctor.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use appropriate media to extinguish.

**Storage**

P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

**Disposal**

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

**Supplemental label information**

EUH208 - Contains 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime. May produce an allergic reaction.

**2.3. Other hazards**

None known.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH.; STRAIGHT RUN KEROSENE [A COMPLEX COMBINATION OF HYDROCARBONS OBTAINED FROM THE DISTILLATION OF CRUDE OIL OR NATURAL GASOLINE. IT CONSISTS PREDOMINANTLY OF SATURATED HYDROCARBONS HAVING CARBON NUMBERS PREDOMINANT	30 - 40	64742-88-7 265-191-7	-	649-405-00-X	
<b>Classification:</b> STOT RE 1;H372, Asp. Tox. 1;H304					
2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime	1 - 5	96-29-7 202-496-6	-	616-014-00-0	
<b>Classification:</b> Acute Tox. 4;H312;(ATE: 1100 mg/kg), Eye Dam. 1;H318, Skin Sens. 1;H317, Carc. 2;H351					
2-Methoxy-1-methylethyl acetate	1 - 5	108-65-6 203-603-9	-	607-195-00-7	#
<b>Classification:</b> Flam. Liq. 3;H226					
Diacetone alcohol	1 - 5	123-42-2 204-626-7	-	603-016-00-1	
<b>Classification:</b> Eye Irrit. 2;H319					
CARBENDAZIM (ISO);METHYL BENZIMIDAZOL-2-YLCARBAMATE	0,1 - 1	10605-21-7 234-232-0	-	613-048-00-8	
<b>Classification:</b> Muta. 1B;H340, Repr. 1B;H360FD, Aquatic Acute 1;H400, Aquatic Chronic 1;H410					
Ethylbenzene	0,1 - 1	100-41-4 202-849-4	-	601-023-00-4	#
<b>Classification:</b> Flam. Liq. 2;H225, Acute Tox. 4;H332;(ATE: 11 mg/l), STOT RE 2;H373, Asp. Tox. 1;H304					

#### List of abbreviations and symbols that may be used above

DSD: Directive 67/548/EEC.

CLP: Regulation No. 1272/2008.

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### Composition comments

The full text for all R- and H-phrases is displayed in section 16.

## SECTION 4: First aid measures

#### General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

#### 4.1. Description of first aid measures

##### Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

##### Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

##### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

##### Ingestion

Call a physician or poison control centre immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

#### 4.2. Most important symptoms and effects, both acute and delayed

Aspiration may cause pulmonary oedema and pneumonitis. Narcosis. Behavioural changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

### SECTION 5: Firefighting measures

#### General fire hazards

Flammable liquid and vapour.

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>).

##### Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

#### 5.3. Advice for firefighters

##### Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

##### Special fire fighting procedures

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

#### Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### For non-emergency personnel

Wear appropriate personal protective equipment.

##### For emergency responders

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Use personal protection recommended in Section 8 of the SDS.

#### 6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

#### 6.3. Methods and material for containment and cleaning up

Use water spray to reduce vapours or divert vapour cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13.

#### 6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapour. Do not get this material in contact with eyes. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

#### 7.3. Specific end use(s)

Not available.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

## Occupational exposure limits

### Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value	Form
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Ceiling	550 mg/m3	
		100 ppm	
	MAK	275 mg/m3 50 ppm	
Aluminium hydroxide (CAS 21645-51-2)	MAK	5 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
	STEL	20 mg/m3	Inhalable fraction.
		10 mg/m3	Respirable fraction.
Diacetone alcohol (CAS 123-42-2)	MAK	240 mg/m3 50 ppm	
Ethylbenzene (CAS 100-41-4)	Ceiling	880 mg/m3	
		200 ppm	
	MAK	440 mg/m3 100 ppm	
Silica, amorphous (CAS 7631-86-9)	MAK	4 mg/m3	Inhalable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	MAK	5 mg/m3	Respirable dust.
	STEL	10 mg/m3	Respirable dust.

### Belgium. Exposure Limit Values

Components	Type	Value	Form
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3	
		100 ppm	
	TWA	275 mg/m3 50 ppm	
Diacetone alcohol (CAS 123-42-2)	TWA	241 mg/m3 50 ppm	
Ethylbenzene (CAS 100-41-4)	STEL	551 mg/m3	
		125 ppm	
	TWA	87 mg/m3 20 ppm	
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TWA	10 mg/m3	

### Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value	Form
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3	
		100 ppm	
	TWA	275 mg/m3 50 ppm	

**Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work**

Components	Type	Value	Form
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3	
	TWA	435 mg/m3	
Kaolin (CAS 1332-58-7)	TWA	6 mg/m3	Inhalable fraction.
		3 mg/m3	Respirable fraction.
Silica, amorphous (CAS 7631-86-9)	TWA	10 mg/m3	Inhalable fraction.
		0,07 mg/m3	Respirable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TWA	10 mg/m3	Respirable dust.

**Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09**

Components	Type	Value	Form
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	MAC	275 mg/m3	
		50 ppm	
	STEL	550 mg/m3 100 ppm	
Diacetone alcohol (CAS 123-42-2)	MAC	241 mg/m3	
		50 ppm	
	STEL	362 mg/m3 75 ppm	
Ethylbenzene (CAS 100-41-4)	MAC	442 mg/m3	
		100 ppm	
	STEL	884 mg/m3 200 ppm	
Kaolin (CAS 1332-58-7)	MAC	2 mg/m3	Respirable dust.
Silica, amorphous (CAS 7631-86-9)	MAC	6 mg/m3	Total dust.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	MAC	0,1 mg/m3 4 mg/m3	Respirable dust.
			Respirable dust.
		10 mg/m3	Total dust.

**Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended.**

Components	Type	Value
Silica, amorphous (CAS 7631-86-9)	TWA	2 mg/m3
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TWA	10 mg/m3

**Czech Republic. OELs. Government Decree 361**

Components	Type	Value
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Ceiling	550 mg/m3
	TWA	270 mg/m3
Diacetone alcohol (CAS 123-42-2)	Ceiling	300 mg/m3
	TWA	200 mg/m3

**Czech Republic. OELs. Government Decree 361**

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	Ceiling	500 mg/m3
	TWA	200 mg/m3

**Denmark. Exposure Limit Values**

Components	Type	Value	Form
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	TLV	275 mg/m3	
		50 ppm	
Diacetone alcohol (CAS 123-42-2)	TLV	240 mg/m3	
		50 ppm	
Ethylbenzene (CAS 100-41-4)	TLV	217 mg/m3	
		50 ppm	
Kaolin (CAS 1332-58-7) titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TLV	2 mg/m3	Respirable.
	TLV	6 mg/m3	

**Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended**

Components	Type	Value	Form
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3	
		100 ppm	
		TWA	275 mg/m3
Diacetone alcohol (CAS 123-42-2)	STEL	50 ppm	
		240 mg/m3	
		TWA	120 mg/m3
Ethylbenzene (CAS 100-41-4)	STEL	25 ppm	
		884 mg/m3	
		TWA	200 ppm
Silica, amorphous (CAS 7631-86-9) titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TWA	442 mg/m3	Fine dust, respiratory fraction
		100 ppm	
		2 mg/m3	
TWA	5 mg/m3		

**Finland. Workplace Exposure Limits**

Components	Type	Value	Form
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3	
		100 ppm	
		TWA	270 mg/m3
Diacetone alcohol (CAS 123-42-2)	STEL	50 ppm	
		360 mg/m3	
		TWA	75 ppm
TWA	240 mg/m3		
	50 ppm		

**Finland. Workplace Exposure Limits**

Components	Type	Value	Form
Ethylbenzene (CAS 100-41-4)	STEL	880 mg/m <sup>3</sup>	
		200 ppm	
	TWA	220 mg/m <sup>3</sup> 50 ppm	
Kaolin (CAS 1332-58-7) titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TWA	2 mg/m <sup>3</sup>	Respirable.
	TWA	10 mg/m <sup>3</sup>	Dust.

**France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984**

Components	Type	Value	Form	
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	VLE	550 mg/m <sup>3</sup>		
	<b>Regulatory status:</b> Regulatory binding (VRC)			
			100 ppm	
	<b>Regulatory status:</b> Regulatory binding (VRC) VME		275 mg/m <sup>3</sup>	
	<b>Regulatory status:</b> Regulatory binding (VRC)		50 ppm	
Diacetone alcohol (CAS 123-42-2)	VME	240 mg/m <sup>3</sup>		
	<b>Regulatory status:</b> Indicative limit (VL)			
			50 ppm	
Ethylbenzene (CAS 100-41-4)	VLE	442 mg/m <sup>3</sup>		
	<b>Regulatory status:</b> Regulatory binding (VRC)			
			100 ppm	
	<b>Regulatory status:</b> Regulatory binding (VRC) VME		88,4 mg/m <sup>3</sup>	
	<b>Regulatory status:</b> Regulatory binding (VRC)		20 ppm	
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	VME	10 mg/m <sup>3</sup>		
	<b>Regulatory status:</b> Regulatory binding (VRC)			
			Indicative limit (VL)	

**Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)**

Components	Type	Value	Form
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	TWA	270 mg/m <sup>3</sup>	
		50 ppm	
Aluminium hydroxide (CAS 21645-51-2)	TWA	4 mg/m <sup>3</sup>	Inhalable dust.
		1,5 mg/m <sup>3</sup>	Respirable dust.
CARBENDAZIM (ISO);METHYL BENZIMIDAZOL-2-YLCAR BAMATE (CAS 10605-21-7)	TWA	10 mg/m <sup>3</sup>	Inhalable fraction.
Diacetone alcohol (CAS 123-42-2)	TWA	96 mg/m <sup>3</sup>	



**Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)**

Components	Type	Value	Form
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
		88 mg/m3	
Silica, amorphous (CAS 7631-86-9)	TWA	4 mg/m3	Inhalable fraction.
Synthetic Amorphous Silica (CAS 112945-52-5)	TWA	4 mg/m3	Inhalable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TWA	0,3 mg/m3	Respirable fraction.

**Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace**

Components	Type	Value	Form
2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime (CAS 96-29-7)	AGW	1 mg/m3	
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	AGW	0,3 ppm	
		270 mg/m3	
CARBENDAZIM (ISO);METHYL BENZIMIDAZOL-2-YLCAR BAMATE (CAS 10605-21-7)	AGW	50 ppm	
Diacetone alcohol (CAS 123-42-2)	AGW	10 mg/m3	Inhalable fraction.
		96 mg/m3	
Ethylbenzene (CAS 100-41-4)	AGW	20 ppm	
		88 mg/m3	
Silica, amorphous (CAS 7631-86-9)	AGW	20 ppm	
		4 mg/m3	Inhalable fraction.

**Greece. OELs (Decree No. 90/1999, as amended)**

Components	Type	Value	Form
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3	
	TWA	100 ppm	
Diacetone alcohol (CAS 123-42-2)	TWA	275 mg/m3	
	STEL	50 ppm	
Ethylbenzene (CAS 100-41-4)	TWA	360 mg/m3	
	STEL	75 ppm	
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TWA	240 mg/m3	
	STEL	50 ppm	
Ethylbenzene (CAS 100-41-4)	TWA	545 mg/m3	
	STEL	125 ppm	
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TWA	435 mg/m3	
	STEL	100 ppm	Respirable.

**Greece. OELs (Decree No. 90/1999, as amended)**

Components	Type	Value	Form
		10 mg/m3	Inhalable

**Hungary. OELs. Joint Decree on Chemical Safety of Workplaces**

Components	Type	Value	
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3	
	TWA	275 mg/m3	
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m3	
	TWA	442 mg/m3	

**Iceland. OELs. Regulation 154/1999 on occupational exposure limits**

Components	Type	Value	Form
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3	
		100 ppm	
	TWA	275 mg/m3	
Diacetone alcohol (CAS 123-42-2)		50 ppm	
	TWA	240 mg/m3	
Ethylbenzene (CAS 100-41-4)		50 ppm	
	STEL	884 mg/m3	
	TWA	200 ppm	
Kaolin (CAS 1332-58-7)		200 mg/m3	
	TWA	50 ppm	
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TWA	2 mg/m3	Respirable dust.
	TWA	6 mg/m3	

**Ireland. Occupational Exposure Limits**

Components	Type	Value	Form
2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime (CAS 96-29-7)	STEL	33 mg/m3	
		10 ppm	
	TWA	10 mg/m3	
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)		3 ppm	
	STEL	550 mg/m3	
	TWA	100 ppm	
Diacetone alcohol (CAS 123-42-2)		275 mg/m3	
	TWA	50 ppm	
Ethylbenzene (CAS 100-41-4)		240 mg/m3	
	STEL	50 ppm	
Kaolin (CAS 1332-58-7)		884 mg/m3	
	TWA	200 ppm	
		442 mg/m3	
Silica, amorphous (CAS 7631-86-9)		100 ppm	
	TWA	2 mg/m3	Respirable dust.
	TWA	6 mg/m3	Total inhalable dust.

**Ireland. Occupational Exposure Limits**

Components	Type	Value	Form
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TWA	2,4 mg/m3	Respirable dust.
		4 mg/m3	Respirable dust.
		10 mg/m3	Total inhalable dust.

**Italy. Occupational Exposure Limits**

Components	Type	Value	Form
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3	
		100 ppm	
		275 mg/m3	
Diacetone alcohol (CAS 123-42-2)	TWA	50 ppm	
		50 ppm	
		50 ppm	
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m3	
		200 ppm	
		442 mg/m3	
Kaolin (CAS 1332-58-7)	TWA	100 ppm	Respirable fraction.
		2 mg/m3	
		10 mg/m3	
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TWA	10 mg/m3	

**Latvia. OELs. Occupational exposure limit values of chemical substances in work environment**

Components	Type	Value
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3
		100 ppm
		275 mg/m3
Aluminium hydroxide (CAS 21645-51-2)	TWA	50 ppm
		6 mg/m3
		6 mg/m3
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m3
		200 ppm
		442 mg/m3
Silica, amorphous (CAS 7631-86-9)	TWA	100 ppm
		1 mg/m3
		1 mg/m3
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TWA	10 mg/m3

**Lithuania. OELs. Limit Values for Chemical Substances, General Requirements**

Components	Type	Value
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	400 mg/m3
		75 ppm
		250 mg/m3
Aluminium hydroxide (CAS 21645-51-2)	TWA	50 ppm
		6 mg/m3
		6 mg/m3

**Lithuania. OELs. Limit Values for Chemical Substances, General Requirements**

Components	Type	Value
Diacetone alcohol (CAS 123-42-2)	STEL	240 mg/m <sup>3</sup>
		50 ppm
	TWA	120 mg/m <sup>3</sup> 25 ppm
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m <sup>3</sup>
		200 ppm
	TWA	442 mg/m <sup>3</sup> 100 ppm
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TWA	5 mg/m <sup>3</sup>

**Luxembourg. Binding Occupational exposure limit values (Annex I), Memorial A**

Components	Type	Value
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m <sup>3</sup>
		100 ppm
	TWA	275 mg/m <sup>3</sup> 50 ppm
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m <sup>3</sup>
		200 ppm
	TWA	442 mg/m <sup>3</sup> 100 ppm

**Malta. OELs. Occupational Exposure Limit Values (L.N. 227. of Occupational Health and Safety Authority Act (CAP. 424), Schedules I and V)**

Components	Type	Value
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m <sup>3</sup>
		100 ppm
	TWA	275 mg/m <sup>3</sup> 50 ppm
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m <sup>3</sup>
		200 ppm
	TWA	442 mg/m <sup>3</sup> 100 ppm

**Netherlands. OELs (binding)**

Components	Type	Value
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	TWA	550 mg/m <sup>3</sup>
Ethylbenzene (CAS 100-41-4)	STEL	430 mg/m <sup>3</sup>
	TWA	215 mg/m <sup>3</sup>

**Norway. Administrative Norms for Contaminants in the Workplace**

Components	Type	Value
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	TLV	270 mg/m <sup>3</sup>
		50 ppm
Diacetone alcohol (CAS 123-42-2)	TLV	120 mg/m <sup>3</sup>

**Norway. Administrative Norms for Contaminants in the Workplace**

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	TLV	25 ppm
		20 mg/m <sup>3</sup>
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TLV	5 ppm
		5 mg/m <sup>3</sup>

**Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817**

Components	Type	Value	Form
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	520 mg/m <sup>3</sup>	
	TWA	260 mg/m <sup>3</sup>	
Aluminium hydroxide (CAS 21645-51-2)	TWA	2,5 mg/m <sup>3</sup>	Inhalable fraction.
		1,2 mg/m <sup>3</sup>	Respirable fraction.
CARBENDAZIM (ISO); METHYL BENZIMIDAZOL-2-YLCAR BAMATE (CAS 10605-21-7)	TWA	10 mg/m <sup>3</sup>	
Diacetone alcohol (CAS 123-42-2)	TWA	240 mg/m <sup>3</sup>	
Ethylbenzene (CAS 100-41-4)	STEL	400 mg/m <sup>3</sup>	
	TWA	200 mg/m <sup>3</sup>	
Kaolin (CAS 1332-58-7)	TWA	10 mg/m <sup>3</sup>	Inhalable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TWA	10 mg/m <sup>3</sup>	Inhalable fraction.

**Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266)**

Components	Type	Value
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m <sup>3</sup>
	TWA	100 ppm 275 mg/m <sup>3</sup>
Ethylbenzene (CAS 100-41-4)	STEL	50 ppm 884 mg/m <sup>3</sup>
	TWA	200 ppm 442 mg/m <sup>3</sup> 100 ppm

**Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)**

Components	Type	Value	Form
Diacetone alcohol (CAS 123-42-2)	TWA	50 ppm	
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Kaolin (CAS 1332-58-7)	TWA	2 mg/m <sup>3</sup>	Respirable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TWA	10 mg/m <sup>3</sup>	

**Romania. OELs. Protection of workers from exposure to chemical agents at the workplace**

Components	Type	Value	Form
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3	
		100 ppm	
	TWA	275 mg/m3 50 ppm	
Diacetone alcohol (CAS 123-42-2)	STEL	250 mg/m3	
		53 ppm	
	TWA	150 mg/m3 32 ppm	
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m3	
		200 ppm	
	TWA	442 mg/m3 100 ppm	
Kaolin (CAS 1332-58-7) titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TWA	2 mg/m3	Respirable fraction.
	STEL	15 mg/m3	
	TWA	10 mg/m3	

**Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents**

Components	Type	Value	Form
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3	
		100 ppm	
	TWA	275 mg/m3 50 ppm	
Aluminium hydroxide (CAS 21645-51-2)	TWA	4 mg/m3	Inhalable fraction.
		1,5 mg/m3	Respirable fraction.
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m3	
		200 ppm	
	TWA	442 mg/m3 100 ppm	
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TWA	5 mg/m3	

**Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

Components	Type	Value	Form
2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime (CAS 96-29-7)	TWA	1 mg/m3	
		0,3 ppm	
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	TWA	275 mg/m3	
		50 ppm	
CARBENDAZIM (ISO); METHYL BENZIMIDAZOL-2-YLCAR BAMATE (CAS 10605-21-7)	TWA	10 mg/m3	Inhalable fraction.

**Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

Components	Type	Value	Form
Diacetone alcohol (CAS 123-42-2)	TWA	96 mg/m3	
		20 ppm	
Ethylbenzene (CAS 100-41-4)	TWA	442 mg/m3	
		100 ppm	
Silica, amorphous (CAS 7631-86-9)	TWA	4 mg/m3	Inhalable fraction.

**Spain. Occupational Exposure Limits**

Components	Type	Value	Form
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3	
		100 ppm	
		275 mg/m3	
Diacetone alcohol (CAS 123-42-2)	TWA	50 ppm	
		241 mg/m3	
		50 ppm	
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m3	
		200 ppm	
	TWA	441 mg/m3	
		100 ppm	
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
		10 mg/m3	
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TWA	10 mg/m3	

**Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)**

Components	Type	Value	Form
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Ceiling	550 mg/m3	
		100 ppm	
		275 mg/m3	
Diacetone alcohol (CAS 123-42-2)	TWA	50 ppm	
		240 mg/m3	
		120 mg/m3	
Ethylbenzene (CAS 100-41-4)	Ceiling	25 ppm	
		884 mg/m3	
		200 ppm	
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TWA	220 mg/m3	
		50 ppm	
		5 mg/m3	Total dust.

**Switzerland. SUVA Grenzwerte am Arbeitsplatz**

Components	Type	Value	Form
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	275 mg/m3	

**Switzerland. SUVA Grenzwerte am Arbeitsplatz**

Components	Type	Value	Form
		50 ppm	
	TWA	275 mg/m3	
		50 ppm	
Aluminium hydroxide (CAS 21645-51-2)	TWA	3 mg/m3	Respirable fraction.
CARBENDAZIM (ISO);METHYL BENZIMIDAZOL-2-YLCAR BAMATE (CAS 10605-21-7)	STEL	40 mg/m3	Inhalable fraction.
	TWA	10 mg/m3	Inhalable fraction.
Diacetone alcohol (CAS 123-42-2)	STEL	192 mg/m3	
		40 ppm	
	TWA	96 mg/m3	
		20 ppm	
Ethylbenzene (CAS 100-41-4)	STEL	220 mg/m3	
		50 ppm	
	TWA	220 mg/m3	
		50 ppm	
Kaolin (CAS 1332-58-7)	TWA	3 mg/m3	Respirable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TWA	3 mg/m3	Respirable dust.

**UK. EH40 Workplace Exposure Limits (WELs)**

Components	Type	Value	Form
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	548 mg/m3	
		100 ppm	
	TWA	274 mg/m3	
		50 ppm	
Diacetone alcohol (CAS 123-42-2)	STEL	362 mg/m3	
		75 ppm	
	TWA	241 mg/m3	
		50 ppm	
Ethylbenzene (CAS 100-41-4)	STEL	552 mg/m3	
		125 ppm	
	TWA	441 mg/m3	
		100 ppm	
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable dust.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TWA	4 mg/m3	Respirable.
		10 mg/m3	Inhalable

**EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU**

Components	Type	Value
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3
		100 ppm



**EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU**

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	TWA	275 mg/m <sup>3</sup>
		50 ppm
	STEL	884 mg/m <sup>3</sup>
		200 ppm
	TWA	442 mg/m <sup>3</sup>
		100 ppm

**Biological limit values**

**Croatia. BLV. Dangerous Substance Exposure Limit Values at Workplace, Annexes 4 (as amended)**

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	1,5 g/g	Mandelic acid	Creatinine in urine	*
	1,5 mg/l	Ethylbenzene	Blood	*
	1,12 mol/mol	Mandelic acid	Creatinine in urine	*
	14,1 umol/l	Ethylbenzene	Blood	*

\* - For sampling details, please see the source document.

**Czech Republic. Limit Values for Indicators of Biological Exposure Tests in Urine and Blood, Annex 2, Tables 1 and 2, Government Decree 432/2003 Sb.**

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	1100 µmol/mmol	Mandelic acid	Creatinine in urine	*
	1500 mg/g	Mandelic acid	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Finland. HTP-arvot, App 2., Biological Limit Values, (BRA/BGV) , Social Affairs and Ministry of Health**

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	5,2 mmol/l	Mandelic acid	Urine	*

\* - For sampling details, please see the source document.

**France. Biological indicators of exposure (IBE) (National Institute for Research and Security (INRS, ND 2065)**

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	1500 mg/g	Acide mandélique	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Germany. TRGS 903, BAT List (Biological Limit Values)**

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	250 mg/g	Mandelsäure plus Phenylglyoxylsäure	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Hungary. Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices**

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	1500 mg/g	mandelic acid	Creatinine in urine	*
	1110 µmol/mmol	mandelic acid	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Slovakia. BLVs (Biological Limit Value). Regulation no. 355/2006 concerning protection of workers exposed to chemical agents, Annex 2**

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	8,03 mg/g	2-ethylphenol	Creatinine in urine	*

**Slovakia. BLVs (Biological Limit Value). Regulation no. 355/2006 concerning protection of workers exposed to chemical agents, Annex 2**

Components	Value	Determinant	Specimen	Sampling Time
	12 mg/l	2-ethylphenol	Urine	*

\* - For sampling details, please see the source document.

**Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4**

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	700 mg/g	Suma del acido mandélico y el ácido fenilglioxílico	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)**

Components	Value	Determinant	Specimen	Sampling Time
Aluminium hydroxide (CAS 21645-51-2)	50 µg/g	Aluminium	Creatinine in urine	*
Ethylbenzene (CAS 100-41-4)	600 mg/g	Mandelsäure plus Phenylglyoxylsäure	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Recommended monitoring procedures** Follow standard monitoring procedures.

**Derived no effect levels (DNELs)** Not available.

**Predicted no effect concentrations (PNECs)** Not available.

**Exposure guidelines**

**EU Exposure Limit Values: Skin designation**

2-Methoxy-1-methylethyl acetate (CAS 108-65-6) Can be absorbed through the skin.  
Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

**Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime (CAS 96-29-7) Can be absorbed through the skin.  
2-Methoxy-1-methylethyl acetate (CAS 108-65-6) Can be absorbed through the skin.  
Diacetone alcohol (CAS 123-42-2) Can be absorbed through the skin.  
Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

**8.2. Exposure controls**

**Appropriate engineering controls** Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

**Individual protection measures, such as personal protective equipment**

**General information** Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection**

**- Hand protection** Wear appropriate chemical resistant gloves.

**- Other** Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

**Respiratory protection** Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**Hygiene measures** Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

**Environmental exposure controls** Environmental manager must be informed of all major releases.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Colour</b>	Pink.
<b>Odour</b>	Mild.
<b>Melting point/freezing point</b>	Not available.
<b>Boiling point or initial boiling point and boiling range</b>	136,11 - 251,67 °C (277 - 485 °F)
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	1,1 %
<b>Flammability limit - upper (%)</b>	7 %
<b>Flash point</b>	4,8 - 40,6 °C (40,6 - 105,0 °F)
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>pH</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Negligible
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Vapour pressure</b>	Not available.
<b>Vapour density</b>	> 1 (air = 1)
<b>Relative density</b>	> 1 @ 70°C
<b>Particle characteristics</b>	Not available.
<b>Other safety characteristics</b>	
<b>Evaporation rate</b>	< 1 (BuAc = 1)
<b>Explosive properties</b>	Not explosive.
<b>Oxidising properties</b>	Not oxidising.
<b>VOC</b>	30,83 %

## SECTION 10: Stability and reactivity

<b>10.1. Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>10.2. Chemical stability</b>	Material is stable under normal conditions.
<b>10.3. Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>10.4. Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>10.5. Incompatible materials</b>	Strong oxidising agents.
<b>10.6. Hazardous decomposition products</b>	Carbon oxides.

## SECTION 11: Toxicological information

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

### Information on likely routes of exposure

<b>Inhalation</b>	May cause damage to organs through prolonged or repeated exposure by inhalation.
<b>Skin contact</b>	May cause an allergic skin reaction.
<b>Eye contact</b>	Causes serious eye damage.
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

**Symptoms** Aspiration may cause pulmonary oedema and pneumonitis. Narcosis. Behavioural changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause an allergic skin reaction. Dermatitis. Rash.

**11.1. Information on toxicological effects**

**Acute toxicity** May be fatal if swallowed and enters airways.

Components	Species	Test Results
------------	---------	--------------

2-Methoxy-1-methylethyl acetate (CAS 108-65-6)

**Acute**

**Dermal**

LD50	Rat	> 2000 mg/kg, 24 Hours
------	-----	------------------------

**Oral**

LD50	Rat	> 5000 mg/kg
------	-----	--------------

CARBENDAZIM (ISO);METHYL BENZIMIDAZOL-2-YLCARBAMATE (CAS 10605-21-7)

**Acute**

**Oral**

LD50	Rat	> 5000 mg/kg
------	-----	--------------

Diacetone alcohol (CAS 123-42-2)

**Acute**

**Oral**

LD50	Rat	3000 mg/kg
------	-----	------------

Ethylbenzene (CAS 100-41-4)

**Acute**

**Oral**

LD50	Rat	3500 mg/kg
------	-----	------------

SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH.; STRAIGHT RUN KEROSENE [A COMPLEX COMBINATION OF HYDROCARBONS OBTAINED FROM THE DISTILLATION OF CRUDE OIL OR NATURAL GASOLINE. IT CONSISTS PREDOMINANTLY OF SATURATED HYDROCARBONS HAVING CARBON NUMBERS PREDOMINANT (CAS 64742-88-7)

**Acute**

**Dermal**

LD50	Rabbit	> 2000 mg/kg, 24 Hours
------	--------	------------------------

**Inhalation**

*Vapour*

LC50	Rat	> 4,5 mg/l, 4 Hours
------	-----	---------------------

**Oral**

LD50	Rat	> 5000 mg/kg
------	-----	--------------

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

**Serious eye damage/eye irritation** Causes serious eye damage.

**Respiratory sensitisation** Not a respiratory sensitizer.

**Skin sensitisation** May cause an allergic skin reaction.

**Germ cell mutagenicity** May cause genetic defects.

**Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

CARBENDAZIM (ISO);METHYL BENZIMIDAZOL-2-YLCARBAMATE (CAS 10605-21-7)	Mutagenic, Category 1B.
--	-------------------------

**Carcinogenicity** Suspected of causing cancer.

**ACGIH Carcinogens**

Ethylbenzene (CAS 100-41-4)	Confirmed animal carcinogen with unknown relevance to humans. A3
-----------------------------	--

**Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)**

CARBENDAZIM (ISO);METHYL BENZIMIDAZOL-2-YLCARBAMATE (CAS 10605-21-7)

**IARC Monographs. Overall Evaluation of Carcinogenicity**

Ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.
-----------------------------	-------------------------------------

**Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime (CAS 96-29-7) Carcinogenic, Category 2.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

**Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

CARBENDAZIM (ISO);METHYL BENZIMIDAZOL-2-YLCARBAMATE (CAS 10605-21-7) Toxic for reproduction, Category 1B.

**Specific target organ toxicity - single exposure** Not classified.

**Specific target organ toxicity - repeated exposure** Causes damage to organs (central nervous system) through prolonged or repeated exposure.

**Aspiration hazard** May be fatal if swallowed and enters airways.

**Mixture versus substance information** No information available.

**11.2. Information on other hazards**

**Endocrine disrupting properties** Not available.

**Other information** Symptoms may be delayed.

**SECTION 12: Ecological information**

**12.1. Toxicity** Based on available data, the classification criteria are not met for hazardous to the aquatic environment, acute hazard. Due to partial or complete lack of data the classification for hazardous to the aquatic environment, long term hazard, is not possible.

Components	Species	Test Results
2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime (CAS 96-29-7)		
<b>Aquatic</b>		
<i>Acute</i>		
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> ) 777 - 914 mg/l, 96 hours
CARBENDAZIM (ISO);METHYL BENZIMIDAZOL-2-YLCARBAMATE (CAS 10605-21-7)		
<b>Aquatic</b>		
<i>Acute</i>		
Fish	LC50	Channel catfish ( <i>Ictalurus punctatus</i> ) 0,008 - 0,013 mg/l, 96 hours
Diacetone alcohol (CAS 123-42-2)		
<b>Aquatic</b>		
<i>Acute</i>		
Fish	LC50	Bluegill ( <i>Lepomis macrochirus</i> ) 420 mg/l, 96 hours
Ethylbenzene (CAS 100-41-4)		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> ) 1,37 - 4,4 mg/l, 48 hours
Fish	LC50	Atlantic silverside ( <i>Menidia menidia</i> ) 4,4 - 5,7 mg/l, 96 hours

**12.2. Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

**12.3. Bioaccumulative potential**

**Partition coefficient**

**n-octanol/water (log Kow)**

CARBENDAZIM (ISO);METHYL BENZIMIDAZOL-2-YLCARBAMATE	1,52
Diacetone alcohol	-0,098
Ethylbenzene	3,15

**Bioconcentration factor (BCF)** Not available.

**12.4. Mobility in soil** Not established.

**12.5. Results of PBT and vPvB assessment** Not a PBT or vPvB substance or mixture.

**12.6. Endocrine disrupting properties** Not available.

**12.7. Other adverse effects** The product contains volatile organic compounds which have a photochemical ozone creation potential.

**12.8. Additional information**

**Estonia Dangerous substances in soil Data**

Ethylbenzene (CAS 100-41-4)

ETHYLBENZENE 0,1 mg/kg

ETHYLBENZENE 5 mg/kg

ETHYLBENZENE 50 mg/kg

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Residual waste** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

**EU waste code** The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Disposal methods/information** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Special precautions** Dispose in accordance with all applicable regulations.

**SECTION 14: Transport information**

**ADR**

**14.1. UN number** UN1263

**14.2. UN proper shipping name** Paint

**14.3. Transport hazard class(es)**

**Class** 3

**Subsidiary risk** -

**Label(s)** 3

**Hazard No. (ADR)** 30

**Tunnel restriction code** D/E

**14.4. Packing group** III

**14.5. Environmental hazards** No.

**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**RID**

**14.1. UN number** UN1263

**14.2. UN proper shipping name** Paint

**14.3. Transport hazard class(es)**

**Class** 3

**Subsidiary risk** -

**Label(s)** 3

**14.4. Packing group** III

**14.5. Environmental hazards** No.

**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**ADN**

**14.1. UN number** UN1263

**14.2. UN proper shipping name** Paint

**14.3. Transport hazard class(es)**

**Class** 3

**Subsidiary risk** -

**Label(s)** 3

**14.4. Packing group** III

**14.5. Environmental hazards** No.

**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**IATA**

**14.1. UN number** UN1263

**14.2. UN proper shipping name** Paint

### 14.3. Transport hazard class(es)

Class 3

Subsidiary risk -

14.4. Packing group III

14.5. Environmental hazards No.

ERG Code 3L

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

### Other information

Passenger and cargo aircraft Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

### IMDG

14.1. UN number UN1263

14.2. UN proper shipping name PAINT

14.3. Transport hazard class(es)

Class 3

Subsidiary risk -

14.4. Packing group III

14.5. Environmental hazards

Marine pollutant No.

EmS F-E, S-E

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

14.7. Maritime transport in bulk according to IMO instruments Not applicable.

ADN; ADR; IATA; IMDG; RID



## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended  
Not listed.

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended  
Not listed.

EU Regulation 648/2004, Annex VII, Content Labeling for Detergents  
Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended  
Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA  
Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended  
CARBENDAZIM (ISO); METHYL BENZIMIDAZOL-2-YLCARBAMATE (CAS 10605-21-7)

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended  
Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended  
Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended  
Ethylbenzene (CAS 100-41-4)

#### Authorisations

**Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**

Not listed.

**Restrictions on use**

**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended**

CARBENDAZIM (ISO);METHYL BENZIMIDAZOL-2-YLCARBAMATE (CAS 10605-21-7)

**Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.**

CARBENDAZIM (ISO);METHYL BENZIMIDAZOL-2-YLCARBAMATE (CAS 10605-21-7)

**Other EU regulations**

**Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended**

2-Methoxy-1-methylethyl acetate (CAS 108-65-6)

CARBENDAZIM (ISO);METHYL BENZIMIDAZOL-2-YLCARBAMATE (CAS 10605-21-7)

Ethylbenzene (CAS 100-41-4)

**Other regulations**

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended. According to Directive 92/85/EEC as amended, pregnant women should not work with the product, if there is the least risk of exposure.

**National regulations**

Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended.

Follow national regulation on the protection of workers from the risks of exposure to carcinogens and mutagens at work, in accordance with Directive 2004/37/EC.

**15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out.

**SECTION 16: Other information**

**List of abbreviations**

Not available.

**References**

Not available.

**Information on evaluation method leading to the classification of mixture**

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

**Full text of any H-statements not written out in full under Sections 2 to 15**

H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H340 May cause genetic defects.  
H351 Suspected of causing cancer.  
H360FD May damage fertility. May damage the unborn child.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.

**Revision information**

Transport Information: Product Shipping Name/Packing Group

**Training information**

Follow training instructions when handling this material.

**Disclaimer**

ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.