



# UV Marker

## STORAGE

- Keep away from open flames, hot surfaces and sources of ignition. Keep containers tightly closed in a cool, well-ventilated place. Keep out of the reach of children. Keep container closed when not in use. Keep away from incompatible materials.

## HANDLING

- Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only in an area containing flame proof equipment. Ensure adequate ventilation.

## DISPOSAL

- Dispose of contents/container to an approved waste disposal plan

## FEATURES

- Applies clear mark barely detectable to the eye
- Excellent for security applications
- Marks on plastic, glass and nonporous surfaces
- Drying Time: 45 seconds to 1 minute



## PHYSICAL PROPERTIES

Appearance / Physical State	Liquid.
Odor	Aromatic
Flash Point	42.22 °C / 108 °F
Boiling Point / Range	158.89-170 °C / 318-338 °F
VOC Content	90.00% 809 g/L
Evaporation Rate	< 1 (BuAc = 1)
Vapor Density	> 1 (air = 1)
Prop 65 Warning	YES

## AVAILABLE IN

Color	Units/Case	Marker Tip	Part #
clear	6	medium, felt (#29)	91195



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved