



Nickel Anti-Seize



FEATURES

- Strong resistance to water wash off
- Can be used with ammonia, acetylene, and vinyl monomers
- Chemically inert
- Protects against seizure, rust, and corrosion
- Does not contain lead, copper, or graphite
- Prevents seizure up to 2600°F (1427°C)
- For use in hostile environments and extreme temperatures
- Acid resistant
- Will not run, drip or settle out
- Silver color

APPLICATIONS

- Bushings
- Chains
- Engines
- Flanges
- Furnaces
- Heat Exchangers
- Manifolds
- Nuts & Bolts
- Screws
- Studs
- Turbines
- Valve Stems

SPECIFICATIONS AND APPROVALS

- MIL-PRF-907E

PROPERTIES

Appearance / Physical State	Paste/Solid
Odor	Slight petroleum odor
Melting / Freezing Point	Not available
Boiling Point / Range	Not available
Vapor Pressure	Not available
Partition Coefficient	Not available
Percent volatile	Not available
Flammability	Not available
Propellant	N/A
VOC Content	none
Color	Silver, grey
Flash Point	< 424.4 °F (< 218.0 °C) Cleveland Open Cup
Density	Not available
Evaporation Rate	Not available
Vapor density	Not available
Auto-Ignition Temperature	Not available
Viscosity	Not available
Specific Gravity	1.18 g/ml
Temperature Range	Not available
4-Ball Weld Load	200

DIRECTIONS

Nickel Anti-Seize is designed for protection in extreme environments and temperatures (including stainless steel). NOTE: Not for use on oxygen systems.

HANDLING

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

STORAGE

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

Dispose of contents/container in accordance with local/regional/national/international regulations.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
03908	C03908	0.5 lb / 227 grams	units	12	8 lbs
03910	C03910	1 lb / 454 grams	units	12	15 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved