


Flame Retardant Aerospace Carpet Tape



- Carrier:** Cloth
- Adhesive:** Natural Rubber Based
- Liner:** Blue LDPE
- Colors:** Natural or Black (adhesive color)
- Specifications:**

FAA	FAR 25.853(a)
Boeing	BMS 5-133, BAC5034-4 Sec 5.1a(1)(b)
Douglas	DMS 1971
Lockheed	LAC C-24-1257
Embraer	MEP 06-048
Fokker	FK05-121, FK05-197
Airbus	ABD0031 Para 7.4
Bombardier	DSC 91-8-1 & DSC 91-8-2
- Standard Sizes:** 48mm x 23m, 72mm x 23m

Applications

- Carpet installation on interior floors and stairs of aircraft
- Hanging and sealing acrylic plastic sheeting
- Mounting, bonding, and securing for general machine shop applications

Features

- Cloth reinforcement
- Flame retardant rubber-based adhesive

Benefits

- Good strength and elongation for easy tear, application and removal
- Conformable and moisture resistant
- Clean removal from most surfaces
- Aggressive bond for secure hold
- Repositionable adhesive for easy installation

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	15.0 mils	0.381 mm	ASTM D-1000
Adhesion to Steel	60 oz/in	6.56 N/cm	PSTC-101
Tensile Strength	55 lb/in	96.32 N/cm	ASTM D-1000
Weight	13 oz/yd ²	472.9 g/m ²	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
Exiting Time	1.5 sec		FAR 25.853(a)
Burn Length	4.5"		FAR 25.853(a)
Drip Exiting	N/A		FAR 25.853(a)

Recommended Storage Conditions: 32-90 °F at 50% RH ± 2%
 Standard Shelf Life (at 25 °C): 24 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.