

Indicator lights with reflector
LED not exchangeable

Signalleuchten mit Reflektor
LED nicht auswechselbar

Voyants lumineux avec réflecteur
LED non remplaçable

13C

14C



Type / Typ / Type		Body / Körper / Corps		Accessories Zubehör Accessoires	Light source Lichtquelle Source lum.	Specifications / Spezifikationen / Spécifications LED's / Leuchtdioden / Diodes lumineuses					
Terminals Anschlüsse Raccords		Surface Oberfläche Surface	Protection Schutzart Protection		LED 3 mm	Electro-optical characteristics Ta = 25°C					
13C		B Blackened geschwärzt Noircie	0	1	R3010 Red Rot Rouge	Colour diffused	Peak wave length λp Typ.	Operating (Storage) Temperatur	Viewing Angle	Typ. mcd	Forward voltage Typ. Max.
		S Bright nickel plated Glanzverni- ckelt Nickelée brillante			G3010 Green Grün Vert		nm	°C	°		V V
					Y3010 Yellow Gelb Jaune		700	- 40 +85 (+100)	40°	8.0	2.2 2.6
14C							568		40°	35	2.2 2.6
							585		40°	40	2.1 2.6

Operating Temperature -30° to +85°C / Storage Temperature: -40° to +100°C

different LED's of the SLOAN range can be built in

Specifications are subject to change without notice – Änderungen die dem technischen Fortschritt dienen, sind vorbehalten – Réserve de modifications de toutes les données techniques

