

Audio Connector, Plug, 6.3 mm, 2-pole, solder terminal, shielded



Description

- Solder terminal: for cable mounting
- Audio entrances and exits
- Data and Signal transfer
- Audio Plug: 2-pole, shielded, straight

References

Alternative: Housing insulated [4833.1210](#); [4833.1220](#)

Weblinks


[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [RoHS](#), [CHINA-RoHS](#), [Mating Connectors](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#)

Technical Data

Diameter	6.3 mm
Number of Poles	2-pole
Ratings DC	1 A / 30VDC
Ratings AC	1 A / 30VAC
Dielectric Strength	500VDC
Insulation Resistance	> 50 MΩ @ 500VDC

Allowable Operation Temp.	-20 °C to 70 °C
Terminal	solder terminal nickel-plated
Housing	screened
Style	straight
Lifetime	5000 Insertions

Dimensions



Variants

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
Audio Plug/Sockets	6.3	2-pole	solder terminal	4833.1200

Packaging unit 500 Pcs

Mating Outlets/Connectors

Category / Description



[Audio Plug/Sockets Overview complete](#)

Audio Connector, Socket, 6.3 mm, 2-pole, solder terminal, shielded	4833.2200
Audio Connector, Socket, 6.3 mm, 2-pole, solder terminals for PCB, shielded	4833.2220
Audio Connector, Socket, 6.3 mm, 2-pole, solder terminals for PCB, insulated	4833.2230
Audio Connector, Plug, Inline Socket, 6.3 mm, 2-pole, solder terminal, insulated	4833.3200

[Audio Plug/Sockets further types to 4833 Audio-Stecker, D=6,3mm](#)