

Audio Connector, Plug, Inline Socket, 6.3 mm, 3-pole, solder terminal, insulated



### Description

- Solder terminal: for cable mounting
- Audio entrances and exits
- Data and Signal transfer
- Audio Plug: 3-pole, insulated, straight


### Weblinks

[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [RoHS](#), [CHINA-RoHS](#), [Mating Connectors](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#)


### Technical Data

Diameter	6.3 mm	Allowable Operation Temp.	-20 °C to 70 °C
Number of Poles	3-pole	Terminal	solder terminal nickel-plated
Ratings DC	1 A / 30VDC	Housing	insulated
Ratings AC	1 A / 30VAC	Style	straight
Dielectric Strength	500VDC	Lifetime	5000 Insertions
Insulation Resistance	> 50 MΩ @ 500VDC		


### Dimensions



Cable diameter max. 6.3 mm



### Diagrams



### Variants

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
Audio Plug/Sockets	6.3	3-pole	solder terminal	4833.3300

Packaging unit 500 Pcs

## Mating Inlets/Plugs

### Category / Description

[Audio Plug/Sockets Overview complete](#)



Audio Connector, Plug, 6.3 mm, 3-pole, solder terminal, shielded	4833.1300
Audio Connector, Plug, 6.3 mm, 3-pole, solder terminal, insulated	4833.1310
Audio Connector, Plug, 6.3 mm, 3-pole, solder terminal, insulated, angled	4833.1320

[Audio Plug/Sockets further types to 4833 Audio-Stecker, D=6,3mm](#)