


EU Power Supply Cord with IEC Connector C19, straight/ angled



Description

- Power Cord, Protection class I
- Pin temperature 70 °C
- custom specific versions on request

Weblinks

[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [RoHS](#), [CHINA-RoHS](#), [Mating Connectors](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#), [Accessories](#)

Technical Data

| | |
|---------------------------|---|
| Ratings IEC | 16 A / 250 VAC; 50 Hz |
| Dielectric Strength | > 4 kVDC between L-N > 2 kVAC between L/N-PE (1 min/50 Hz) |
| Allowable Operation Temp. | -25 °C to 70 °C |
| Degree of Protection | from front side IP 20 acc. to IEC 60529 |
| Protection Class | Suitable for appliances with protection class I acc. to IEC 61140 |
| Terminal | moulded |
| Material: Housing | PVC, black |

| | |
|-----------|--|
| Connector | C19 acc. to IEC 60320 UL 498, CSA C22.2 no. 42 (for cold conditions) pin-temperature 70 °C, 16 A, Protection Class I |
|-----------|--|

Variants

| Connector | | cable | | | | Plug | | | | | Order Number |
|-----------|--------|-------------|-------------------------|------------|-------|----------|---------|-------------|--------|-------|--------------|
| Type | V-Lock | Cord Type | Conductor cross section | Length [m] | Color | Type | Country | Standard | Style | Index | |
| C19 | | H05W-F3G1.5 | 3 x 1.5 mm ² | 2.5 | black | Europlug | EU | CEE 7 / VII | angled | - | 6004.0395 |

Most Popular.

Availability for all products can be searched real-time: <http://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

Packaging unit 30 Pcs

Mating Inlets/Plugs

Category / Description

[Appliance Inlet Overview complete](#)



| | |
|---|------|
| IEC Appliance Inlet C20, Screw-on Mounting, Rear Side, PCB Terminal | 1601 |
| IEC Appliance Inlet C20, Screw-on Mounting, Front Side, Solder, Quick-connect or Screw Terminal | 1621 |
| IEC Appliance Inlet C20, Snap-in Mounting, Front Side, Solder or Quick-connect Terminal | 4793 |
| IEC Appliance Inlet C24, Snap-in Mounting, Front Side, Solder or Quick-connect Terminal | 4794 |
| IEC Appliance Inlet C20, Screw-on Mounting, Front Side, Solder or Quick-connect Terminal | 4798 |

[Appliance Inlet further types to Cord Sets 15 A](#)



Appliance inlets/-outlets Overview complete

| | |
|---|------|
| Plug Coupler IEC C20 / IEC J, Screw-on Mounting | 4730 |
|---|------|

Appliance inlets/-outlets further types to Cord Sets 15 A



Plug Overview complete

| | |
|---|------|
| IEC Plug I, Cord Connector (Rewireable), Angled | 4789 |
|---|------|

| | |
|---|------|
| IEC Plug I, Cord Connector (Rewireable), Straight | 4796 |
|---|------|

Plug further types to Cord Sets 15 A



Power Entry Module Overview complete

| | |
|--|------|
| IEC Appliance Inlet C20 with Circuit Breaker TA35 1-pole | 6136 |
|--|------|

| | |
|--|------|
| IEC Appliance Inlet C20 with Line Switch, 2-pole | EC11 |
|--|------|

| | |
|---|------|
| IEC Appliance Inlet C20 with Circuit Breaker TA45 | EF11 |
|---|------|

Power Entry Module further types to Cord Sets 15 A



Power Entry Module with line filter Overview complete

| | |
|--|------|
| IEC Appliance Inlet C20 with Filter, Front or Rear Side Mounting | C20F |
|--|------|

| | |
|---|------|
| IEC Appliance Inlet C20 with Filter, Line Switch 2-pole | EC12 |
|---|------|

| | |
|--|------|
| IEC Appliance Inlet C20 with Filter, Circuit Breaker TA45 (recessed) | EF12 |
|--|------|

| | |
|--|------|
| | EG12 |
|--|------|

Power Entry Module with line filter further types to Cord Sets 15 A