


IEC Interconnection cord with IEC Connector C21, straight

new



Description

- Power Cord, Protection class I
- Pin temperature 155 °C
- custom specific versions on request

Weblinks

[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [RoHS](#), [CHINA-RoHS](#), [Mating Connectors](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#), [Accessories](#)

Technical Data

Ratings IEC	16 A / 250 VAC; 50/60 Hz
Allowable Operation Temp.	-40 °C to 105 °C
Degree of Protection	from front side IP 40 acc. to IEC 60529
Protection Class	Suitable for appliances with protection class I acc. to IEC 61140
Material: Housing	black

Connector	C21 acc. to IEC 60320 UL 498, CSA C22.2 no. 42 (for very hot conditions) pin-temperature 155 °C, 16 A, Protection Class I
-----------	--

Variants

Connector						cable					Plug				Order Number
Type	V-Lock	Cord Type	Conductor cross section	Length [m]	Color	Type	Country	Standard	Style	Index					
C21		H05VV-F3G1.5 / SJT 3x14 AWG	3 x 1.5 mm ² / 3 x 14 AWG	2.0	black	IEC Connector	INT	IEC 60320-2-2	straight	-					6051.5003

Most Popular.

Availability for all products can be searched real-time: <http://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

Packaging unit 50 Pcs

Mating Inlets/Plugs

Category / Description



[Appliance Inlet Overview complete](#)

IEC Appliance Inlet C22, Screw-on or Snap-in Mounting, Front Side, Quick connect, Solder or Screw Terminal

1681

[Appliance Inlet further types to Cord Sets 15 A](#)



[Power Entry Module with line filter Overview complete](#)

IEC Appliance Inlet C22 for Hot Conditions, with Filter for High Temperatures, Front Side Mounting

C22F

[Power Entry Module with line filter further types to Cord Sets 15 A](#)