

DC Fan Specification



D6010L12B/S

1. MODEL NUMBER
2. CATEGORY
3. FRAME SIZE
4. RATED VOLTAGE
5. OPERATING VOLTAGE RANGE
6. START-UP VOLTAGE
7. RATED MOTOR SPEED
8. AIR FLOW
9. STATIC PRESSURE
10. RATED CURRENT
11. RATED INPUT POWER
12. NOISE LEVEL
13. DIRECTION OF ROTATION
14. OPERATING TEMPERATURE
15. STORAGE TEMPERATURE
16. BEARING SYSTEM
17. LIFE EXPECTANCY
18. SAFETY APPROVAL
19. WEIGHT

D6010L12B(X1)
 BRUSHLESS DC FAN
 60 x 60 x 10 mm (2.4 x 2.4 x 0.4 inch)
 12 VDC
 6 V ~ 13.8V
 6 V / Min.
 3000 RPM $\pm 10\%$
 12.0 CFM (0.34 m³/Min.)
 1.84 mm/H₂O (0.07 inch/H₂O)
 0.14 Amp $\pm 10\%$
 1.68 Watts $\pm 10\%$
 23.83 dB(A)
 Clockwise viewed from front label
 -10°C ~ + 70°C / 66% (RH)
 -40°C ~ + 75°C / 66% (RH)
 BALL BEARING
 70,000 Hrs
 UL, CUL, TUV, CE
 23 gm

D6010L12S(X1)
 BRUSHLESS DC FAN
 60 x 60 x 10 mm (2.4 x 2.4 x 0.4 inch)
 12 VDC
 6 V ~ 13.8V
 6 V / Min.
 3000 RPM $\pm 10\%$
 12.0 CFM (0.34 m³/Min.)
 1.84 mm/H₂O (0.07 inch/H₂O)
 0.14 Amp $\pm 10\%$
 1.68 Watts $\pm 10\%$
 23.83 dB(A)
 Clockwise viewed from front label
 -10°C ~ + 70°C / 66% (RH)
 -40°C ~ + 75°C / 66% (RH)
 SLEEVE BEARING
 30,000 Hrs
 UL, CUL, TUV, CE
 23 gm

