

PAG.M0.2GL.AC52R

Status

Size/Series P / 1P

Matching

[Request a quote](#)

MECHANICAL DETAILS

Shell Style/Model PA*: Straight plug with cable collet
Keying 1 key (alpha=0; Plug: male contact; Receptacle: female contact)
Housing Material PSU (Polysulfone), gray
Cable Fixing C52: 4 - 5.2 mm
Variant R : Red collet nut

PERFORMANCE DETAILS

Insert Configuration 1P.M02 : 2 Low Voltage
Contact Type: Solder
Max. Matings: 2000
Contact Dia.: 1.3 mm (0.0512in)
Bucket Dia.: 1.1 mm (0.04in)
Max. Solid Conductor: 0.5 mm² (AWG 20)
Max. Stranded Conductor: 0.5 mm² (AWG 20)
R (max): 3.5 mOhm
Rated Current (A): 10
Test voltage (kV rms) 1.2
Contact-contact:
Air clearance min. (mm) 1.3
or Creepage distance min. (mm):

OTHER CHARACTERISTICS

Endurance (Shell)
F ret (min): 50 N
F ret (max): 150 N
IP Rating 50

[Catalog](#)



[Download 3D draw](#)

mm. 14 0.55
in.

L 45 1.77

